





양산 단계
이 모델은 양산 단계에 있으며 장기간 구매 및 사용이 가능합니다.



사양

센서

센서 타입	CMOS 컬러
셔터	Global Shutter
센서 특성	선형의
픽셀 등급	2 MP
해상도	2.30 Mpix
해상도 (h x v)	1920 x 1200 픽셀
종횡비	16:10
ADC	10 bit
색 심도(카메라)	10 bit
광학 센서 등급	1/2.6"
광학 영역	5.760 mm x 3.600 mm
광학 센서 대각선	6.79 mm 1/2.6"
픽셀 크기	3 μm
CRA (주광선 각도)	0 °
제조사	Onsemi
센서 모델	AR0234CSSC00SUKA0
게인(마스터/RGB)	9.5x/15.1x
AOI 수평	동일한 프레임 레이트
AOI 수직	프레임 레이트 증가
AOI 이미지 너비/단차 너비	48 / 12
AOI 이미지 높이/단차폭	4 / 2
AOI 위치 그리드(수평/수직)	4 / 2
수평 비닝	프레임 레이트 증가
수직 비닝	프레임 레이트 증가
비닝 방법	수평: 합산 / 수직: 합산
비닝 요소	2x2
수평 decimation (서브샘플링)	프레임 레이트 증가
수직 decimation (서브샘플링)	프레임 레이트 증가
decimation (서브샘플링) 방법	M/C 자동



모델

프레임 레이트 프리런 모드	101 fps
프레임 레이트 트리거(연속)	100 fps
프레임 레이트 트리거(최대)	100 fps
노출 시간(최소 - 최대)	0.012 ms - 446 ms
전력 소비	0.5 W - 1 W
이미지 메모리	-

주변 조건들

PCB 버전들의 경우, 각각의 문서 내의 별도 힌트들을 참조하십시오.


작동 중 허용되는 장치 온도	0 °C - 85 °C / 32 °F - 185 °F
보관 중 허용되는 장치 온도	-20 °C - 80 °C / -4 °F - 176 °F
습도(상대, 비응축)	20 % - 80 %

커넥터들

인터페이스 커넥터	USB 3.0 micro-B
I/O 커넥터	8-핀 Wuerth 커넥터
전력 공급	USB 케이블

핀 할당 I/O 커넥터

1	전압 출력 3.3 V
2	접지 (GND)
3	오토커풀러 없이 플래시 출력 - Line 1
4	오토커풀러 없이 트리거 입력 - Line 0
5	범용 I/O (GPIO) 1 - Line 2
6	범용 I/O (GPIO) 2 - Line 3
7	접지 (GND)
8	USB 전원: 5 V, 최대 400 mA



디자인

렌즈 마운트	No mount
IP 코드	-
치수 H/W/L	29.0 mm x 29.0 mm x 6.4 mm
무게	7 g
하우징 자재	-

Features

카메라 내 이미지 사전 처리 기능 목록입니다.

표의 모든 기능은 호스트 컴퓨터에서 이미지 전처리를 위한 IDS peak 소프트웨어를 통해 사용할 수 있습니다(센서 모델에 따라 다름).

이미지 획득

Freerun	✓
Software trigger	✓
Hardware trigger	✓
Trigger controlled exposure	-
Denoiser	-
Long exposure	-
Line scan	-

깜박임

Flashing	✓
PWM flashing	-

이미지 조정	Auto exposure	-
	Auto gain	-
	Auto whitebalance	-
	Color correction	-
	Gamma	-
	LUT	-
	Mirror/flip	X/Y

온보드 이미지 처리	Pixel formats	BayerGR8 BayerGR10g40IDS
	Region of interest	✓
	Decimation (FPGA)	-
	Decimation (Sensor)	
	Binning (FPGA)	-
	Binning (Sensor)	2x2 Increases frame rate.

기타	Chunks	-
	Sequencer	-
	Events	-
	Firmware update	✓
	1st supported firmware version	3.2